DCK

NEW

POWERED BY LI-ION TECHNOLOGY

20V MAX Li-ion

LARGER CAPACITY

longer run time

CHARGING AND DISCHARGING MONITORING

over-discharge and overcharge protection for longer battery life



Your power source

FFBL2080

20V 8.0AH BATTERY

Voltage	20V
Capacity	8.0Ah
Charging time	2A 4h/4A 2h
Net Weight	0.98kg

DCK

NEW

SURGING POWER

efficient cutting

AUTOMATIC OIL PUMPING

HIGH-QUALITY CARBURETOR

stable quality

QUICK BRAKING SYSTEM

effectively protect the safety of operators



Powerful Cutting Performance

K04YD45

PETROL CHAIN SAW

Power Input	1700W
Displacement	45ml
Power	2-Stroke Air Cooling
Blade Type	18“
Pitch	0.325”
Net Weight	5.4kg

DCK

NEW

SURGING POWER

efficient cutting

AUTOMATIC OIL PUMPING

HIGH-QUALITY CARBURETOR

stable quality

QUICK BRAKING SYSTEM

effectively protect the safety of operators



Powerful Cutting Performance

K04YD54

PETROL CHAIN SAW

Power Input	2300W
Displacement	54.5ml
Power	2-Stroke Air Cooling
Blade Type	20“
Pitch	0.325”
Net Weight	5.4kg

DCK

NEW

SURGING POWER

efficient cutting

AUTOMATIC OIL PUMPING

HIGH-QUALITY CARBURETOR

stable quality

QUICK BRAKING SYSTEM

effectively protect the safety of operators



Overwhelming performance

K04YD58

PETROL CHAIN SAW

Power Input	2900W
Displacement	55.6ml
Power	2-Stroke Air Cooling
Blade Type	20“
Pitch	0.325”
Net Weight	5.4kg

DCK

NEW EC BRUSHLESS MOTOR POWERED BY LI-ION TECHNOLOGY 20V MAX Li-ion

BRUSHLESS MOTOR

higher efficiency and longer service life

AUTOMATIC OIL PUMPING



RUBBER-COVERED HANDLE

comfortable to hold



TOOL-LESS CHAIN TIGHTNESS ADJUSTMENT

convenient to ues



Compact yet powerful

KDML250

(TYPE FK/BM/DM/Z)

CORDLESS BRUSHLESS CHAIN SAW

(TYPE FK) 5.0Ah×2, 4A Charger
(TYPE BM) 4.0Ah×2, 2A Charger
(TYPE DM) 4.0Ah×1, 2A Charger
(TYPE Z) Solo, Color Box Packing


Battery	20V MAX/5.0Ahx2/4.0Ahx2/4.0Ahx1/Solo
No-load Speed	10m/s
Max. Length of Guide Bar	255mm
Net Weight	2.9/2.9/2.9/2.3kg

DCK

NEW EC BRUSHLESS MOTOR POWERED BY LI-ION TECHNOLOGY 20V MAX Li-ion

BRUSHLESS MOTOR

more powerful, higher efficiency
and longer runtime and lifetime




ADJUSTTABLE 0-45° BEVER CUTTING ANGLE

meet different cutting requirements

ANTI-RESTART FUNCTION

ensure the security of the operator



2-SPEED

match various
applications



ULTRA-SLIM BODY DESIGN

comfortable to grip

Compact design for perfect handling

KDMY125

(TYPE FK/BM/DM/Z)

CORDLESS BRUSHLESS CIRCULAR SAW

(TYPE FK) 5.0Ah×2, 4A Charger
(TYPE BM) 4.0Ah×2, 2A Charger
(TYPE DM) 4.0Ah×1, 2A Charger
(TYPE Z) Solo, Color Box Packing

Battery	20V MAX/5.0Ahx2/4.0Ahx2/4.0Ahx1/Solo	
No-load Speed	Low	4200r/min
	High	6700r/min
Blade Dia.		125mm
Max.cutting Capacity		0° 45mm
		45° 33mm
Max.cutting Angle		45°
Net Weight		2.4/2.4/2.4/1.8kg

DCK

NEW


POWERED BY LI-ION TECHNOLOGY

12V MAX Li-ion



INTELLIGENT DIGITAL DISPLAY

accurate monitoring of air pressure



LED LIGHT

work in dim environment

LOW NOISE AND LOW VIBRATION

TIRE PRESSURE SETTING AND MONITORING FUNCTION

all under you master





COMPACT

convenient to carry

A mobile pneumatic energy station

KDQE120

(TYPE DK/Z)

CORDLESS AIR PUMP

(TYPE DK) 2.0Ah×1, 3A Charger
(TYPE Z) Solo, Color Box Packing

Battery	12V/2.0Ah×1/Solo
No-load Speed	13000r/min
Max. air pressure	8.3Bar
Net Weight	1.05/0.85kg

DCK

NEW

POWERED BY LI-ION TECHNOLOGY

20V MAX Li-ion

BRUSHLESS MOTOR

high temperature resistance,
longer service life



RUBBER-COVERED HANDLE

comfortable to hold



HIGH, LOW AND TURBO GEAR

meet the needs of different
working environment





LARGE AIR VOLUME

strong power

Storm in you hand

KDQF20091

(TYPE FK/BM/DM/Z)

CORDLESS BRUSHLESS BLOWER

(TYPE FK) 5.0Ah×2, 4A Charger
(TYPE BM) 4.0Ah×2, 2A Charger
(TYPE DM) 4.0Ah×1, 2A Charger
(TYPE Z) Solo, Color Box Packing

Battery	20V MAX/5.0Ahx2/4.0Ahx2/4.0Ahx1/Solo
No-load Speed	5000-16000(Turbo Gear 21500)r/min
Air Volume	1.9-6.5(Turbo Gear 8.4)m^3/min
Net Weight	1.9/1.9/1.9/1.3kg

DCK

NEW

UPGRADED MODEL OF KZC02-28

for longer lifetime and optimized sealing structure



LARGE TRIGGER SWITCH, SDS-PLUS



OPTIMAL DRILLING CAPACITY IN CONCRETE

Φ10-Φ20mm

TWO FUNCTIONS

rotary hammer and demolition



RECOMMENDED APPLICATION SCENARIOS

home decoration, industrial decoration, pipeline Laying

Make tough jobs easier

KZC02-28S

ELECTRIC ROTARY HAMMER

Rated Power Input	960W
Impact Energy	3.2J
No-load Speed	1000r/min
Rated Impact Frequency	5000/min
Max. Drilling Capacity	Concrete Φ28mm
Net Weight	5.0kg

DCK

NEW

UPGRADED MODEL OF KZC03-26B

for longer lifetime and optimized sealing structure



LARGE TRIGGER SWITCH, SDS-PLUS



OPTIMAL DRILLING CAPACITY IN CONCRETE

Φ8-Φ18mm

TWO FUNCTIONS

rotary hammer and demolition



RECOMMENDED APPLICATION SCENARIOS

home decoration, industrial decoration, pipeline Laying

Make tough jobs easier

KZC03-26S

ELECTRIC ROTARY HAMMER

Rated Power Input	750W
Impact Energy	3.0J
No-load Speed	700r/min
Rated Impact Frequency	3200/min
Max. Drilling Capacity	Concrete Φ26mm
Net Weight	5.0kg