

# DCA




**12V**  
Lithium-Ion

**EC**

**BRUSHLESS**



## EXCELLENT PERFORMANCE WITH ULTRA COMPACT BODY



### BRUSHLESS MOTOR

Delivering up to 50N·m of torque and 1800/min no-load speed

**21<sub>+2</sub>**

### 21+2 TORQUE SETTING

For a variety of applications



### 10mm RATCHET METAL CHUCK

Sturdy and durable



### 152mm COMPACT BODY

Perfect control in narrow space



### REINFORCED TAIL CAP FOR DURABILITY

Target Users: Woodworkers, Door or Window Installer, Decoration Workers, Electricians

## ADJZ1250i

**CORDLESS BRUSHLESS  
DRIVER/HAMMER DRILL  
TYPE(EK/Z)**



[ Type EK ] 2.0Ahx2, 3A Charger  
[ Type Z ] Solo, Carton Packing

|                        |                  |            |
|------------------------|------------------|------------|
| Battery                | 12V/2.0Ahx2/Solo |            |
| Max. Power Output      | 280W             |            |
| Max. Chucking Capacity | 10mm             |            |
| Impact Frequency       | 0-28800/min      |            |
| No-load Speed          | Low              | 0-500/min  |
|                        | High             | 0-1800/min |
| Max. Drilling Dia.     | Steel            | Φ10mm      |
|                        | Brick Wall       | Φ10mm      |
|                        | Wood             | Φ32mm      |
| Torque Setting         | 21+2             |            |
| Max. Torque            | 50N·m            |            |
| Net Weight             | 1.1/0.9kg        |            |



# DCA



**4V**  
Lithium-Ion



## NO MORE SHAKING



**FULL RUBBER OVERMOLD HOUSING**  
Helping to protect major impact points



**HIGH INTENSITY GREEN LASER**  
For clearer display



**SMART PENDULUM SYSTEM**  
Self levels and indicates  
out-of-level condition up to  $\pm 3^\circ$



**360 ° BIDIRECTIONAL FINE ADJUSTMENT BASE**  
Applicable to different scenarios



**THICKENED ALUMINUM BASE**  
Sturdy and durable



Target Users: Installation of Doors and Windows、 Tile Placement、 Mural Installation

### ADTX4V-11/ 21/41

GREEN LASER LEVEL



[ Type EK ] 2.0Ahx2, 3A Charger  
[ Type Z ] Solo, Carton Packing

|                       |                         |
|-----------------------|-------------------------|
| Power Supply          | 4V/4.0Ah                |
| Laser Diode           | 512nm                   |
| Vertical Accuracy     | 5m $\pm$ 1mm            |
| Leveling Accuracy     | 5m $\pm$ 1mm            |
| Auto-leveling Range   | $\pm 3^\circ$           |
| Leveling Range        | $\geq 120^\circ$        |
| Vertical Range        | $\geq 120^\circ$        |
| Width of Laser Line   | 2.5mm at distance of 5m |
| Operating Temperature | -10°C—40°C              |
| Laser Class           | 3R                      |
| Tripod Thread         | 5/8"                    |
| Net Weight            | 1.0kg                   |

